TECHNICAL DATA SHEET



Trade name : PRALLETHRIN

CHEMICAL IDENTIFICATION

Nomenclature

ISO 1750	:	Prallethrin (mixture of stereoisomers)	
IUPAC	:	(1S)-2-methyl-4-oxo-3-(prop-2-yn-1-yl)cyclopent-2-en-1-yl (1R)-cis-trans-2,2- dimethyl-3-(2-methylprop-1-en-1-yl)cyclopropane-1-carboxylate	
CAS (9 th CI)	:		
Others	:		
CAS number		23031-36-9 (unresolved stereochemistry)	
		(d-cis,trans Prallethrin of d-isomer: 204244-85-9,	
		d-trans of d-isomer: 103065-19-6)	
EC number		: 245-387-9	
Molecular form	nula	: C ₁₉ H ₂₄ O ₃	
Molecular weig	ht	: 300.40	
Structural form (unspecified ste		chemistry)	

PRODUCT SPECIFICATIONS

Purity (ENDQC-91 method by HRGC) : 93.0 % w/w min.

- Isomeric distribution
 - trans-chrysanthemates
 - d-chrysanthemates
- d-prallethronyl chrysanthemates :

Acidity number (ENDQC-96 method) :

Appearance (ENDQC-94 method) :

- 80.0 % min.* :
- 96.0 % min.* :
- 98.0 % min.*
- 5.0 mg KOH/g max.
 - Yellow to brown transparent viscous liquid

Relative % of isomers

NOTE: Endura reserves the right to make amendments to the data reported in this sheet either in compliance to any official body's updating or in agreement with Internal Company decisions. The reported information is, to the best of our knowledge, as accurate and complete as possible and is given in good faith but without warranty from our part. Any use for Registration purposes must be authorised by Endura in advance.

TECHNICAL DATA SHEET



Trade name : PRALLETHRIN

ADDITIONAL INFORMATION				
Odour	: Slightly aromatic			
Density	: 1.03 g/cm ³ at 20 °C			
Vapour pressure	: <1.5 x 10 ⁻⁷ hPa at 25 °C			
Solubility	: Practically insoluble in water Soluble in most common organic solvents			
Partition coefficient (Log Pow)	: >2.78C			

NOTE: Endura reserves the right to make amendments to the data reported in this sheet either in compliance to any official body's updating or in agreement with Internal Company decisions. The reported information is, to the best of our knowledge, as accurate and complete as possible and is given in good faith but without warranty from our part. Any use for Registration purposes must be authorised by Endura in advance.